NO.

CENTRILIFT PART# SE25872T02

PHASOR[™] VSD TRANSFORMER PATENTS 6,734,772 AND 6,787,704

THIS TRANSFORMER IS DESIGNED SPECIFICALLY TO INTERFACE BETWEEN A VARIABLE SPEED DRIVE AND AN ELECTRIC SUBMERSIBLE PUMP. IT IS ALSO SUITABLE FOR OTHER STEP-UP OR STEP DOWN APPLICATIONS. THIS PLATE DISPLAYS THE BASIC RATINGS. SEE OTHER INFORMATION PLATES FOR ADDITIONAL RATINGS AND INFORMATION.

1000 KVA 3 PHASE 60 HERTZ 65°C RISE

	VOLTS	AMPS	CONDUCTOR	BIL
LOW	480	1202	CU	30
HIGH	1260 - 4988	458 - 116	CU	60


3.5 % IMPEDANCE @ 85°C

1.0 % RESISTANCE 3.4 % REACTANCE

354 GAL. MINERAL OIL NON-PCB CLASS OA TANK IS DESIGNED FOR 7 PSIG

OIL LEVEL IS 7" BELOW THE LID AT 25°C OIL LEVEL CHANGES 0.44" PER 10°C

TOTAL MASS 9255 LB.
OIL MASS 2656 LB.
UNTANKING MASS 4473 LB.
TANK AND FITTINGS MASS 2126 LB.





BARCODE THE 13 DIGITS OF P.N. ONLY IN FORMAT 128, 0.25" HEIGHT HUMAN READABLE TEXT, WITH DASHES, IN 0.1" HEIGHT USE BLACK BARCODE

GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED LINEAR ± .063 IN (1/16) WIEDAMATIC ± .031 IN DIAGONAL ± .093 IN (3/32) PORCELAIN ± .03 PER IN

	` ' '					
В	11/02/10	CHANGED LOGO	ST	ST		
Α	12/23/09	ADDED BARCODE	ST	ST		
REV.	DATE	REVISION	BY	APP.		





MADE IN USA

NAME:	T.A.P.	S. VSD	NAME	EPLAT	E 1	C.C.	714
DESCR:	Ş	99341	00390	16			
	3WBT7	001			61506	033.	942
SCALE	1.000	DWG BY	TB	CHK B	Y	DATE	02/24/05